

PCTWORLD INTELLECTUAL PROPERTY ORGANIZATION
International Bureau

INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification 6 : B01F 17/00, C10M 173/00, 173/02, C09G 1/16, A61K 7/00		(11) International Publication Number: WO 95/15812
A1		(43) International Publication Date: 15 June 1995 (15.06.95)
(21) International Application Number: PCT/US94/13887		(81) Designated States: US, European patent (AT, BE, CH, DE, DK, ES, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE). Published <i>With international search report. Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.</i>
(22) International Filing Date: 5 December 1994 (05.12.94)		
(30) Priority Data: 08/163,981 6 December 1993 (06.12.93) US		
(60) Parent Application or Grant (63) Related by Continuation US 08/163,981 (CIP) Filed on 6 December 1993 (06.12.93)		
(71) Applicant (for all designated States except US): STEPAN COMPANY [US/US]; 22 West Frontage Road, Northfield, IL 60093 (US).		
(72) Inventors; and (75) Inventors/Applicants (for US only): RYKLIN, Irma [US]; 405 Woodbury Road, Buffalo Grove, IL 60089 (US). SAJIC, Branko [US/US]; 7227 North Kildare Avenue, Lincolnwood, IL 60646 (US).		
(74) Agent: SARUSSI, Steven, J.; Allegretti & Witcoff, Ltd., Ten South Wacker Drive, Chicago, IL 60606 (US).		

(54) Title: **WATER-IN-OIL EMULSIONS CONTAINING INCREASED AMOUNTS OF OIL AND METHODS FOR PREPARING SAME**

(57) Abstract

Water-in-oil emulsions are disclosed that comprise: a) water; b) from about 10 to 65 % by weight of an oil; and c) an emulsification system comprising a polysiloxane polyalkyl polyether copolymer and a phthalic anhydride derivative, substantially permanently maintaining the water and oil as an emulsion, the emulsification system being substantially free from aluminum and zirconium salts, the emulsion being at a pH of from about 5 to 10.

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AT	Austria	GB	United Kingdom	MR	Mauritania
AU	Australia	GE	Georgia	MW	Malawi
BB	Barbados	GN	Guinea	NE	Niger
BE	Belgium	GR	Greece	NL	Netherlands
BF	Burkina Faso	HU	Hungary	NO	Norway
BG	Bulgaria	IE	Ireland	NZ	New Zealand
BJ	Benin	IT	Italy	PL	Poland
BR	Brazil	JP	Japan	PT	Portugal
BY	Belarus	KE	Kenya	RO	Romania
CA	Canada	KG	Kyrgyzstan	RU	Russian Federation
CF	Central African Republic	KP	Democratic People's Republic of Korea	SD	Sudan
CG	Congo	KR	Republic of Korea	SE	Sweden
CH	Switzerland	KZ	Kazakhstan	SI	Slovenia
CI	Côte d'Ivoire	LI	Liechtenstein	SK	Slovakia
CM	Cameroon	LK	Sri Lanka	SN	Senegal
CN	China	LU	Luxembourg	TD	Chad
CS	Czechoslovakia	LV	Latvia	TG	Togo
CZ	Czech Republic	MC	Monaco	TJ	Tajikistan
DE	Germany	MD	Republic of Moldova	TT	Trinidad and Tobago
DK	Denmark	MG	Madagascar	UA	Ukraine
ES	Spain	ML	Mali	US	United States of America
FI	Finland	MN	Mongolia	UZ	Uzbekistan
FR	France			VN	Viet Nam
GA	Gabon				

-1-

WATER-IN-OIL EMULSIONS CONTAINING INCREASED
AMOUNTS OF OIL AND METHODS FOR PREPARING SAME

5

BACKGROUND OF THE INVENTION

Field of the Invention

The present invention relates to water-in-oil emulsions containing increased amounts of an oil phase. More specifically, the invention relates to water-in-oil emulsions comprising oil and water phases and an emulsifier comprising a phthalic anhydride derivative that are stable at critical pH values.

Description of the Related Art

Water-in-oil emulsions have been employed in a wide variety of applications. Among these are polishes and waxes for hard surfaces of, for example, automobiles, shoes, and furniture. Water-in-oil emulsions are also used as antiperspirants, sunscreens, skin creams and lotions, and hair treatment compositions such as hair conditioners.

Incorporation of increased amounts of oil, and especially silicone oil, leads to difficulty in preparing stable water-in-oil formulations. It is particularly difficult to formulate stable water-in-oil emulsions having in excess of 50% by weight silicone oil. Thus, formulations of water-in-oil systems with oils such as silicones requires the use of an emulsification system capable of providing the requisite emulsion stability.

U.S. Patent No. 5,188,823 discloses water-in-oil antiperspirant formulations comprising silicone oils, copolyols, phthalamic acids and/or ammonium phthalamates, and

-2-

aluminum and zirconium antiperspirant salts. Water-in-oil formulations containing at most about 33% cyclomethicones are disclosed having viscosities ranging from about 2,700 to 14,000 cps. The pH of these water-in-oil formulations is from about 3.5 to 4.5.

U.S. Patent No. 5,015,415 teaches conditioning shampoos comprising phthalamic acids and/or ammonium phthalamates and silicone oils. Shampoo formulations are disclosed with no more than 0.50% silicone oil. These formulations are taught to be stable at pH values between 3 and 9.

Canadian Patent Application 2,056,859 discloses hair treatment compositions comprising a water-in-oil emulsion, wherein the water phase constitutes 40-95% by weight of the composition and the oil phase 5-60% by weight of the composition, wherein the oil phase comprises a silicone material having a viscosity of 10^4 to 10^9 mPas at 25°C.

SUMMARY OF THE INVENTION

It has been unexpectedly discovered that stable water-in-oil emulsions can be prepared to contain in excess of about 50% by weight oil when the emulsion is formulated with a specific emulsification system and the resulting emulsion is at a specific critical pH. The emulsions of the invention can be prepared to contain any amount of an oil up to about 65% by weight of the formulation.

The water-in-oil emulsions encompassed by the invention comprise:

- (a) water;
- (b) from about 10 to 65% by weight of an oil; and

-3-

(c) an emulsification system comprising a polysiloxane polyalkyl polyether copolymer and a phthalic anhydride derivative, the emulsification system substantially permanently maintaining the water and oil as an emulsion, and the emulsification system being substantially free from aluminum and zirconium salts, the emulsion being at a pH of from about 5-10.

The invention encompasses stable water-in-oil emulsions having viscosities in the range of from about at least 1000, and preferably from about 1500 to 10^6 cps. The invention also encompasses such emulsions that are pastes, i.e., emulsions that are typically not a pourable liquid at ambient temperature.

15 DETAILED DESCRIPTION OF THE INVENTION

Water-in-oil emulsions, and in particular, water-in-oil emulsions containing silicone, are difficult to prepare without separation into oil and water phases when the amount of the oil approaches 50% by weight. The present invention provides novel water-in-oil emulsions that are stable when containing more than 50% by weight of an oil phase. These emulsions employ an emulsification system comprising a specific phthalic anhydride derivative and a silicone glycol surfactant. Further, the pH of the emulsion must be within the critical range to obtain the requisite stability.

25 The oil phase

Water-in-oil compositions of the invention comprise from 5-65% by weight, more preferably from 10-65% by weight, most

-4-

preferably 20-60% by weight of an oil phase. The oil phase may comprise any oily material that is immisible with water. Suitable oily materials are those having viscosities from about 0.1 to 10,000,000 cps. In preferred embodiments of the invention, the oily material is a silicone oil material.

The silicone material for use in compositions of the invention can be any silicone material of the required viscosity. For example, polyalkyl siloxanes, polyalkylaryl siloxanes, aminofunctional silicones, polydiorganosiloxanes or mixtures thereof may be used.

Silicone gums i.e., non volatile silicones, may be used as the silicone materials. For the purpose of the present invention, the term silicone gum denotes polydiorganosiloxanes having a molecular weight of 200,000 to 2,000,000. Examples of suitable silicone gums are for example described in U.S. Patent No. 4,152,416. Specific examples of suitable silicone gums are polydimethyl or polydiphenyl siloxane polymers.


Such silicone materials for use in the compositions of the invention have a viscosity of 10^4 to 10^9 mpa.s at 25°C, more preferably from 5×10^4 to 5×10^8 , most preferably from 10^5 to 5×10^7 mPa.s. A suitable method for measuring the viscosity is by means of a glass capillary viscometer (of Dow Corning CTM 0004), or by a Brookfields synchroelectric viscometer (cf Dow Corning CTM 0050).

In certain embodiments of the invention, the oil phases of compositions also comprise a carrier or diluent material for the high viscosity, non-volatile silicone material. Often, high viscosity silicone materials are supplied as a dispersion in a carrier or diluent material, for example as a

-5-

5-25% by weight dispersion of the high viscosity silicone in cyclomethicone, linear dimethicone and/or isoparaffin. These dispersions may advantageously be used in the oil phase of the hair treatment products of the invention. Alternatively or additionally the oil phase may comprise further diluents such as for example low viscosity silicones (having a viscosity of say between 0.1 to 1,000 mPa.s, more preferably 0.5 to 500 mPa.s most preferably 0.65-100), liquid paraffins or methicones and other solvents such as C₁₀ to C₁₂ isoparaffins such as Isopar L (Esso), polyisobutene such as polysynlane (Nippon Oils and Fats), squalane such as Squalene (J.G. Marthens), branched chain hydrocarbons e.g., Permethyl 99A (Presperse), branched chain light paraffin oils such as Lytol (Witco) or WM1 (BP), mineral oil such as Marchol 82 (Esso) or Carnation Oil (Witco), long chain alkyl alkanoic esters such as decyl oleate (e.g., Cetiol V ex Henkel), isopropyl myristate (e.g., Estol 1514 ex Unichema) and glyceryl tri(2-ethyl hexanoate) e.g., Myritol CTEG ex Henkel).

In preferred embodiments, the silicone oil will comprise a cyclomethicone or dimethicone. Generally such silicones may be represented by the formula:



wherein R is a 1 to 3 carbon alkyl group, n is a number from 3 to 10, preferably from 3 to 7, and the unsatisfied valences on the oxygen and silicon atoms at the ends of the chain may be joined to one another to form a cyclic structure. Suitable

-6-

volatile silicones are, for example, U.C.C. Y-7207, sold by Union Carbide Corporation in which each R is methyl and which typically comprises by weight 99.4% tetramer, 0.6% trimer and traces of the pentamer and hexamer; SWS-03314, sold by SWS Silicones, a Division of Stauffer Chemical Company, in which R is methyl and which is substantially all tetramer; and Dow Corning 344 fluid, sold by Dow Corning, Inc., in which R is methyl and which typically comprises by weight about 88% tetramer, about 11.8% pentamer and traces of trimer and hexamer.

In addition, other volatile silicones may also be utilized, alone or in combination with non-volatile silicones.


It is also possible to employ vegetable oils, animal oils, provided that branched-chain alkyl groups are present as well as various petroleum products and lubricants. Compositions may also be prepared to contain graphite lubricants, polybutene, polyethylene, linseed oil, and crude oil, as well as other oils and other solid or semi-solid materials.

The oils that may be used in the emulsions also include petroleum distillates, solvents and hydrocarbons such as, for example, mineral spirits, kerosene, terpenes, and glycol ethers. The oils may also be materials suitable for personal care products, e.g., mineral oil, petrolatum, caprylic/capric triglyceride, isopropyl myristate, isopropyl palmitate, octyl palmitate, octyl isonononoate alkyl, esters of fatty acids having at least about 16 carbon atoms, lanolin, or alkyl esters of long chain fatty acids.

The oil phase normally is prepared to contain a phthalic

-7-

anhydride derivative emulsifying agent. The phthalic anhydride derivative of the invention has the following formula:



where X a cation is selected from the group consisting of

5 hydrogen ion, $^+NH_2R_3R_4$ where R_3 and R_4 are the same or different and represent hydrogen or straight or branched chain alkyl groups having 8-40 carbon atoms, $[NH_3(R_5OH)]^+$, $[NH_2(R_5OH)_2]^{++}$, $[NH(R_5OH)_3]^+$ where each R_5 is a straight or branched chain alkylene group having from 1-6 carbon atoms, NH_4^+ , $R_7NH_3^+$,

10 $(R_7)_2NH_2^+$, $(R_7)_3NH^+$ where each R_7 is straight or branched chain alkyl having from about 1 to 6 carbon atoms, Na^+ , K^+ , Ba^{++} , Ca^{++} , Mg^{++} , Al^{2+} , and Zn^{2+} , or $(R_7)_2NH_2^+$ represents a heterocyclic cation containing 4 or 5 carbon atoms that optionally contains an oxygen or an additional nitrogen atom,

15 R_1 and R_2 are the same or different and represent straight or branched chain alkyl groups having 1-40 carbon atoms, cycloalkyl groups having 3-18 carbon atoms, straight or branched chain alkenyl groups having 2-40 carbon atoms, alkylaryl groups where the alkyl portion is a straight or

20 branched chain alkyl group having 1-6 carbon atoms and the aryl portion contains 5 to 10 carbon atoms, aryl alkyl where the alkyl portion is a straight or branched chain alkyl of 1-6 carbon atoms and the aryl portion contains 5 to 10 carbon

-8-

atoms, or aryl groups having 5 to 10 carbon atoms, or R_5-O-R_6 where R_5 and R_6 are the same or different and represent straight or branched chain alkyl or alkenyl groups having 1-22 carbon atoms.

5 In a preferred emulsion of the invention, X is $^+NH_2R_3R_4$, and R_1 , R_2 , R_3 , and R_4 are derived from hydrogenated tallow. Because tallow is a mixture of C_{14} to C_{18} fatty acids, and amines derived from tallow are hence a mixture of tallow amines, the phthalamic acids and/or the ammonium salts thereof
10 used in the present invention may therefore have R groups that are the same or different.

In particularly preferred emulsions of the present invention, the formulations comprise N,N-di(hydrogenated) tallow phthalamic acid di(hydrogenated) tallow ammonium salt.
15 In other particularly preferred embodiments, the formulations comprise a mixture of N,N-di(hydrogenated) tallow phthalamic acid and N,N-di(hydrogenated) tallow phthalamic acid di(hydrogenated) tallow ammonium salt. Other formulations comprise N,N-distearyl phthalamic acid and N,N-distearyl
20 phthalamic acid N,N-distearyl ammonium salt where the stearyl groups are derived from a vegetable oil.

The effective concentration of these phthalamic acid ammonium salts and mixtures of the phthalamic acids and phthalamic acid ammonium salts in the emulsions of the present
25 invention vary from about 1% to about 20% on an active basis. A presently preferred use concentration appears to be between about 1% to 5%.


Emulsions of the present invention comprising a mixture

-9-

of phthalmic acid ammonium salt and a phthalamic acid having ratios of acid to salt varying from about 90:10 to about 10:90. Preferred ratios of acid to salt vary from about 70:30 to about 20:80. Particularly preferred ratio of salt to acid is about 80:20.

The emulsification systems of the invention also comprise polysiloxane polyalkyl polyether copolymers, i.e., silicone glycol surfactants which are also known as copolyols. The amount of silicone glycol surfactant is preferably about 0.5 to 15% by weight. A more preferable amount of the silicone glycol surfactant is about 0.5-5% of the composition.

Suitable silicone surfactants are for example high molecular weight polymers of dimethyl polysiloxane with polyoxyethylene and/or polyoxypropylene side chains, having a molecular weight of from 10,000 to 50,000 and having the structure:



wherein the groups R' are each chosen from -H, C₁₋₁₈ alkyl and R'' is -[CH₂CH₂O]_a[CH₂(CH₂)CHO]_bH, in which

- a has a value of from 9 to 115,
- b has a value of from 0 to 50,
- x has a value of from 133 to 673,
- y has a value of from 25 to 0.25.

Preferably, the polymer is an alkoxyated polydimethyl polymer

-10-

in which:

- a has a value of from 10 to 114,
- b has a value of from 0 to 49,
- x has a value of from 388 to 402,
- 5 y has a value of from 15 to 0.75,
- the group R" having a molecular weight of from 1000 to 5000.

A more preferred alkoxyated dimethyl polysiloxane polymer is one in which:

- 10 a has the value 14,
- b has the value 13,
- x has the value 249,
- y has the value 1.25.

A particularly preferred copolyol is cetyl dimethicone
15 copolyol, available from T.H. Goldschmidt as Abil® EM-90.

In addition to the high viscosity silicone material, carrier or diluent material (if any) and emulsification system, the oil phase may also comprise further ingredients such as, for example, perfume oils, coloring agents, and
20 preservatives, etc.

The aqueous phase

Water-in-oil compositions of the invention comprise from 35-95% by weight, more preferably from 40-80% by weight, most preferably from 40-75% by weight of an aqueous phase.

25 Preferably the aqueous phase comprises 20-100% by weight of water, more preferred 30-80%, most preferred 50-70% by weight, based on the weight of the aqueous phase.

In addition to water, the aqueous phase may for example

-11-

comprise one or more liquid water-miscible materials. Suitable materials are for example lower alcohols such as ethanol, and polyols such as propylene glycol, glycerol, sorbitol and polyglycerol. Suitable is the use of polyether materials such as for example polyether materials such as for example polyethyleneglycol or polypropylene glycol having a molecular weight of 100 to 500, ethoxylated polyols, e.g. Atlas G2330 ex ICI and Glucum E10 ex Amerchol and block copolymers of ethylene oxide and propylene oxide e.g. Synperonic L13 or ICI. Other humectants and/or optical brighteners may also be used.

Preferably the aqueous phase comprises 0-75% by weight of liquid water-miscible materials, more preferably 20-65%, most preferably 30-45%, based on the weight of the aqueous phase.

Another preferred ingredient for incorporation in the aqueous phase is an electrolyte material, for example selected from water soluble salts such as alkali (earth) metal salts such as sulphates, halogenides, formates, borates, benzoates, and (C₁₋₄)tetra-alkyl ammonium halides etc. Water soluble acids such as citric acid, phosphoric acid etc. may also be used. The preferred level of electrolyte materials is from 0-25%, more preferred 1-10%, most preferred 2-5%, based on the aqueous phase. Electrolyte materials have the advantage of providing increased stability to compositions of the invention and can be used for modification of composition viscosity.

Physical form

Water-in-oil emulsions according to the invention may take a variety of physical forms, for example they may be

-12-

✓
liquids, gels, pastes, etc. Preferably emulsions of the invention are gels having a viscosity of 5000 to 10^9 , more preferably 10,000 to 200,000 at 25°C, as measured in a Brookfield RVT viscometer, spindle #5, 50 rpm.

5 Other ingredients

Water-in-oil emulsions of the invention may also include minor amounts of other ingredients such as surfactants, antibacterial agents, antidandruff agents, pearlescers, dyes, preservatives, sunscreens, viscosity modifiers, proteins,
10 polymers, buffering agents, herb extracts, oils etc.

Other components that may be included in the emulsions include ultraviolet protection agents such as benzophenones, octyl salicylate, octyl methoxy cinnamate, and para-aminobenzoic acid, amido carboxylates (functionalized metallo
15 soaps) such as lauryl succinamate aluminum stearate (lactate) (see e.g., U.S. Patents Nos. 4,675,422 and 4,724,174), vitamins, and cationic surfactants. Other additives can be optionally suspended in the emulsions, e.g., graphite, abrasives such as kaopolite and snow floss silica, and waxes
20 such as carnuba wax, paraffin wax and microcrystalline waxes.

Method of Preparation

Water-in-oil emulsions of the invention may be prepared by any suitable method for the preparation of water-in-oil emulsions. A preferred method involves the separate
25 preparation of the oil phase and the aqueous phase by mixing, followed by gradually adding the aqueous phase to the oil phase under stirring.

-13-

Subsequent to adding the aqueous phase to the oil phase, the pH of the mixture must be raised to a value of about 5-10. In more preferred water-in-oil emulsions, the pH is about 7-9. The pH of the mixture prior to raising it to a value within
5 the critical range is typically about 2-3. At this acidic pH, the emulsions of the invention having higher amounts of oil are unstable.

The desired pH value can be attained by addition of any suitable basic compound. Examples of such compounds include
10 organic amines and various hydroxide salts. Representative amines are, for example, monoethanolamine, diethylamine and triethanolamine, as well as triethylamine. Suitable hydroxide salts include sodium, potassium and ammonium hydroxide. A particularly preferred base is triethanolamine (TEA).

15 The invention is illustrated further by the following examples which are not to be construed as limiting the invention in scope or spirit to the specific procedures described in them.

EXAMPLE 1

20 Water-in-oil emulsions were prepared by first preparing an oil phase comprising the phthalic anhydride derivative, Stepan TAB®-2, a 30:65 mixture of N,N-di(hydrogenated) tallow ammonium N,N-di(hydrogenated) tallow phthalamate and N,N-di(hydrogenated) tallow phthalamic acid, (unless specifically
25 excluded in comparative examples), silicone glycol surfactant, and oil and heating to about 160-165°F, subsequently preparing an aqueous phase at 160-165°F and adding it to the oil phase. After the aqueous phase has been added to the oil phase, the

-14-

mixture is mixed for about 2-5 minutes at which time the base is added in an amount sufficient to attain the requisite pH. This mixture was emulsified for 25 to 30 minutes while maintaining the temperature between 150-155°F. At this time, additional oil may be added to the emulsion and homogenization performed as needed.

The component amounts in the formulations of the following examples are given in weight percent.

Example 2

10	<u>INGREDIENTS</u>	<u>Wt. % (AS IS)</u>
	Silicone DC 344 (Cyclomethicone)	20.0
	Stepan TAB-2 ¹	3.0
	Abil EM-90 ²	2.0
15	Silicone DC 200 (350 CPS) (Dimethicone)	5.0
	Triethanolamine 99%	Q.S. to pH 8.5
	DI Water	Q.S. to 100.0

¹ A blend of N,N-di(hydrogenated) tallow phthamic acid and N,N-di(hydrogenated) tallow ammonium N,N-di(hydrogenated) tallow phthalamate and triethanolammonium N,N-di(hydrogenated) tallow phthalamate and an acid to salt weight ratio of 60 to 40.

² Cetyl dimethicone copolyol.

-15-

The following Table 1 shows the stability of formulations prepared essentially according to Example 1 at varying levels of phthalamate and silicone surfactant.

TABLE 1

		STABILITY					
		24 hours		one week		3 freeze thaw cycles	
	% TAB-2	% Abil EM-90	room temp.	42°C	room temp.		42°C
5	-	2.0	sep. ¹	sep.	-	-	Fail
	3.0	-	sep.	sep.	-	-	Fail
	0.5	2.0	sep.	sep.	-	-	Pass
	1.0	2.0	stable	sep.	stable	-	Pass
10	2.0	2.0	stable	stable	stable	sep.	Pass
	3.0	1.0	stable	stable	stable	sep.	Pass
	3.0	2.0	stable	stable	stable	stable	Pass
	4.0	2.0	stable	stable	stable	stable	Pass
	4.0	3.0	stable	stable	stable	stable	Pass
15	5.0	2.0	stable	stable	stable	stable	Pass
	20.0	2.0	stable	stable	stable	stable	Pass
	3.0	20.0	stable	sep.	stable	sep.	Pass

1 emulsion separated into oil and water layers

-16-

Table 2 shows the stability of compositions prepared with different ratios of cyclomethicone and dimethicone and the total level of the two silicones.

TABLE 2

		STABILITY					
5	% volatile silicone ¹	% dimethicone ²	24 hours		one week		3 Freeze-thaw cycles
			RT	42°C	RT	42°C	
	4.0	1.0	sep.	sep.	-	-	Fail
	8.0	2.0	sep.	sep.	-	-	Fail
	16.0	4.0	stable	stable	stable	stable	Pass
10	20.0	5.0	stable	stable	stable	stable	Pass
	30.0	3.0	stable	stable	stable	stable	Pass
	40.0	3.0	stable	stable	stable	stable	Pass
	48.0	12.0	stable	stable	sep.	sep.	Pass
	56.0	14.0	sep.	sep.	-	-	Fail
15	1	Silicone DC 344 or DC345					
	2	Silicone DC 200					

-17-

Table 3 shows the effect of varying the base on the stability of emulsions.

TABLE 3

STABILITY

Neutralizing Agent	24 hours		one month	
	room temp.	42°C	room temp.	42°C
5 Monoethanolamine	stable	stable	stable	stable
Triethanolamine	stable	stable	stable	stable
NaOH	stable	stable	stable	stable
Morpholine	stable	sep.	stable	-
NH ₄ OH	stable	stable	stable	sep.

-18-

Table 4 shows the effect of varying the pH on the stability of emulsions having essentially the same composition as Formula 1.

TABLE 4

5

10

15

pH ¹	Stability				
	24 hours		one week		3 Freeze-Thaw Cycles
	RT	42°C	RT	42°C	
2.5 ²	sep.	sep.	sep	sep.	Fail
3.5	stable	stable	sep.	stable	Fail
4.5	stable	stable	stable	stable	Fail
5.5	stable	stable	stable	stable	Pass
6.5	stable	stable	stable	stable	Pass
8.0	stable	stable	stable	stable	Pass
9.0	stable	stable	stable	stable	Pass
10.0	stable	stable	stable	stable	Pass

1 unless indicated otherwise, each specific pH value was attained by addition of sufficient neutralizing agent (triethanolamine)

2 no triethanolamine present

-19-

Auto polish formulations were prepared essentially as described above to have the following compositions.

Table 5

	Ingredient	A Wt. %	B Wt. %	C Wt. %	D Wt. %
5	Silicone DC 344	25.0	30.0	30.0	20.0
	Stepan TAB 2	1.5	1.5	1.0	3.0
	Abil EM-90	1.0	1.0	0.75	2.0
	Silicone DC 200 (50 cps)	3.0	-	-	-
10	Silicone DC 200 (100 cps)	-	2.0	-	-
	Silicone DC 200 (5000 cps)	-	-	1.0	-
	Silicone GE 1706 ¹	-	-	-	5.0
15	Triethanolamine, 99%	all Q.S. to pH 8.5			
	DI Water	all Q.S. to 100%			
	<u>24 hour stability</u>				
	room temperature	stable	stable	stable	stable
	42°C	stable	stable	stable	stable
20	<u>one week stability</u>				
	room temperature	stable	stable	stable	stable
	42°C	stable	stable	stable	stable
	Stability after three freeze-thaw cycles	Pass	Pass	Pass	Pass
25	1 aminofunctional silicone				

-20-

Auto polish emulsions were prepared essentially as described above to have the following compositions.

Table 6

	Ingredient	A	B	C
		Wt. %	Wt. %	Wt. %
5	Isopar M	-	-	10.0
	Mineral Spirits	5.0	25.0	-
	Stepan TAB-2	1.0	1.0	3.0
	Abil EM-90	0.75	0.75	2.0
	Silicone DC200 (350	3.0	3.0	5.0
10	cps)			
	Silicone DC 344	25.0	-	10.0
	Triethanolamine, 99%		all Q.S. to pH 8.5	
	DI Water		all Q.S. to 100%	

-21-

Water-in-oil personal care emulsions were prepared essentially as described above to have the following compositions.

Table 7

	Ingredient	A Wt. %	B Wt. %	C Wt.%	D Wt. %	E Wt%
5	Silicone DC 344		20.0	20.0	20.0	
	Silicone DC 200 (350 cps)		5.0			2.5
	Stepan TAB-2	2.0	3.0	1.5	1.5	1.5
10	Abil EM-90	1.0	1.0	1.0	1.0	1.0
	Octyl Palmitate	20.0				
	Isopropyl Palmitate		10.0			
	White Petrolatum				5.0	15.0
	Lanolin			5.0		
15	Methyl Paraben ¹	0.15	0.15	0.15	0.15	0.15
	Propyl Paraben ²	0.01	0.01	0.01	0.01	0.01
	Glydant ³	0.25	0.25	0.25	0.25	0.25
	Triethanolamine, 99%		all Q.S. to pH 7.0			
	DI Water		all Q.S. to 100.0			
20	1	water soluble preservative				
	2	oil soluble preservative				
	3	preservative				

-22-

Lubricant-containing emulsions were prepared essentially as described above to have the following compositions.

Table 8

5	Ingredient	A	B	C
		Wt. %	Wt. %	Wt. %
	TAB-2	3.0	3.0	2.0
	Abil EM-90	2.0	2.0	1.5
	PB/Graphite ¹	15.0	15.0	
	Ethylflow PAO-170 ²			60.0
10	Indapol L-14 ³	10.0		
	Stepan C68 ⁴		10.0	10.0
	Triethanolamine, 99%	Q.S. to pH 9.0		
	DI Water	Q.S. to 100.0		
15	1 polybutene/graphite (lubricant)			
	2 polyalpha olefin (lubricant)			
	3 polybutene			
	4 methyl esters of fatty acids having 18 carbon atoms (10% saturated, 11% diunsaturated, 70% monounsaturated, and 9% other)			

20 From the foregoing it will be appreciated that, although specific embodiments of the invention have been described herein for purposes of illustration, various modifications may be made without deviating from the spirit and scope of the invention.

-23-

WHAT IS CLAIMED IS:


1. A water-in-oil emulsion comprising:
 - (a) water;
 - (b) from about 10 to 65% by weight of an oil; and
 - 5 (c) an emulsification system comprising a polysiloxane polyalkyl polyether copolymer and a phthalic anhydride derivative,
 the emulsification system substantially permanently maintaining the water and oil as an emulsion, and the

10 emulsification system being substantially free from aluminum and zirconium salts, the emulsion being at a pH of from about 5-10.

2. An emulsion according to Claim 1, wherein the oil is a dimethicone, cyclomethicone, amodimethicone or a mixture

15 thereof.

3. An emulsion according to Claim 2, wherein the phthalic anhydride derivative has the formula:



- where X a cation is selected from the group consisting of hydrogen ion, $^+NH_2R_3R_4$ where R_3 and R_4 are the same or different

20 and represent hydrogen or straight or branched chain alkyl groups having 8-40 carbon atoms, $[NH_3(R_5OH)]^+$, $[NH_2(R_5OH)_2]^{++}$, $[NH(R_5OH)_3]^+$ where each R_5 is a straight or branched chain

-24-

alkylene group having from 1-6 carbon atoms, NH_4^+ , R_7NH_3^+ , $(\text{R}_7)_2\text{NH}_2^+$, $(\text{R}_2)_3\text{NH}^+$ where each R_7 is straight or branched chain alkyl having from about 1 to 6 carbon atoms, Na^+ , K^+ , Ba^{++} , Ca^{++} , Mg^{++} , Al^{2+} , and Zn^{2+} , or $(\text{R}_7)_2\text{NH}_2^+$ represents a
5 heterocyclic ring containing 4 or 5 carbon atoms and oxygen or an additional nitrogen atom, R_1 and R_2 are the same or different and represent straight or branched chain alkyl groups having 1-40 carbon atoms, cycloalkyl groups having 3-18 carbon atoms, straight or branched chain alkenyl groups having
10 2-40 carbon atoms, alkylaryl groups where the alkyl portion is a straight or branched chain alkyl group having 1-6 carbon atoms and the aryl portion contains 5 to 10 carbon atoms, aryl alkyl where the alkyl portion is a straight or branched chain alkyl of 1-6 carbon atoms and the aryl portion contains 5 to
15 10 carbon atoms, or aryl groups having 5 to 10 carbon atoms, or $\text{R}_5\text{-O-R}_6$ where R_5 and R_6 are the same or different and represent straight or branched chain alkyl or alkenyl groups having 1-22 carbon atoms.

4. An emulsion according to Claim 2, wherein the
20 phthalic anhydride derivative is selected from the group consisting of N,N-di(hydrogenated) tallow phthalamic acid, N,N-di(hydrogenated) tallow ammonium N,N-di(hydrogenated) tallow phthalamate, triethanolammonium N,N-di(hydrogenated) tallow phthalamate, N,N-distearyl phthalamic acid, N,N-
25 distearyl phthalamic acid N,N-distearyl ammonium salt, and mixtures thereof.

-25-

5. An emulsion according to Claim 4, wherein the phthalic anhydride derivative is selected from the group consisting of mixtures of N,N-di(hydrogenated) tallow ammonium N,N-di(hydrogenated) tallow ammonium N,N-di(hydrogenated) tallow phthalamate and N,N-di(hydrogenated) tallow phthalamic acid at salt:acid weight ratios of about 80:20, and mixtures of N,N-distearyl phthalamic acid and N,N-distearyl ammonium N,N-distearyl phthalamate.
6. An emulsion according to Claim 3, wherein the oil comprises a mixture of cyclomethicone and dimethicone at a ratio of cyclomethicone to dimethicone of from about 1:3 to 60:1.
7. An emulsion according to Claim 6, wherein the polysiloxane polyalkyl polyether copolymer is a blend of cetyl dimethicone copolyol and cetyl dimethicone.
8. An emulsion according to Claim 7, wherein the phthalic anhydride derivative is a mixture of N,N-di(hydrogenated) tallow ammonium N,N-di(hydrogenated) tallow ammonium N,N-di(hydrogenated) tallow phthalamate and N,N-di(hydrogenated) tallow phthalamic acid at a salt acid weight ratio of about 80:20.
9. An emulsion according to Claim 8, wherein the pH of the emulsion is from about 5-10.

-26-

10. An emulsion according to Claim 9, wherein the pH is from about 7-9.

11. A method for preparing a water-in-oil emulsion comprising the steps:

- 5 (a) preparing an oil phase by mixing an oil with an emulsification system comprising a phthalic anhydride derivative, polysiloxane polyalkyl polyether copolymer and a the emulsification system being substantially free from aluminum and zirconium salts;
- 10 (b) preparing an aqueous phase;
- (c) adding the aqueous phase to the oil phase with agitation;
- (d) raising the pH to from about 5 to 10; and
- 15 (e) emulsifying the mixture.


12. A method according to Claim 11, further comprising a homogenization step.

13. A method according to Claim 11, wherein the oil is a dimethicone, cyclomethicone, amodimethione or a mixture thereof.

20

-27-

14. A method according to Claim 13, wherein the phthalic anhydride derivative has the formula:



where X a cation is selected from the group consisting of hydrogen ion, $^+NH_2R_3R_4$ where R_3 and R_4 are the same or different and represent hydrogen or straight or branched chain alkyl groups having 8-40 carbon atoms, $[NH_3(R_5OH)]^+$, $[NH_2(R_5OH)_2]^{++}$, $[NH(R_5OH)_3]^+$ where each R_5 is a straight or branched chain alkylene group having from 1-6 carbon atoms, NH_4^+ , $R_7NH_3^+$, $(R_7)_2NH_2^+$, $(R_7)_3NH^+$ where each R_7 is straight or branched chain alkyl having from about 1 to 6 carbon atoms, Na^+ , K^+ , Ba^{++} , Ca^{++} , Mg^{++} , Al^{2+} , and Zn^{2+} , R_1 and R_2 are the same or different and represent straight or branched chain alkyl groups having 1-40 carbon atoms, cycloalkyl groups having 3-18 carbon atoms, straight or branched chain alkenyl groups having 2-40 carbon atoms, alkylaryl groups where the alkyl portion is a straight or branched chain alkyl group having 1-6 carbon atoms and the aryl portion contains 5 to 10 carbon atoms, aryl alkyl where the alkyl portion is a straight or branched chain alkyl of 1-6 carbon atoms and the aryl portion contains 5 to 10 carbon atoms, or aryl groups having 5 to 10 carbon atoms, or R_5-O-R_6 where R_5 and R_6 are the same or different and represent straight or branched chain alkyl or alkenyl groups having 1-22 carbon atoms.

-28-

15. A method according to Claim 14, wherein the phthalic anhydride derivative is selected from the group consisting of mixtures of N,N-di(hydrogenated) tallow ammonium N,N-di(hydrogenated) tallow ammonium N,N-di(hydrogenated) tallow phthalamate and N,N-di(hydrogenated) tallow phthalamic acid at
5 salt:acid weight ratios of about 80:20, and mixtures of N,N-distearyl phthalamic acid and N,N-distearyl ammonium N,N-distearyl phthalamate.

16. A method according to Claim 15, wherein the oil
10 comprises a mixture of cyclomethicone and dimethicone at a ratio of cyclomethicone to dimethicone of from about 1:3 to 60:1.

17. A method according to Claim 16, wherein the pH is raised to from about 7-9.

INTERNATIONAL SEARCH REPORT

International Application No.
PCT/US 94/13887

A. CLASSIFICATION OF SUBJECT MATTER

IPC 6 B01F17/00 C10M173/00 C10M173/02 C09G1/16 A61K7/00

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 6 B01F C10M C09G A61K

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US,A,5 188 823 (I.SHAPIRO) 23 February 1993 cited in the application see column 5, line 17 - column 6, line 19 see column 6, line 63 - column 7, line 49	1-8, 11-13
Y	see column 10, line 37 - line 68; examples 5-7	9,10
Y	--- US,A,5 015 415 (J,M.GOZE) 14 May 1991 cited in the application see column 7, line 57 - column 8, line 60	9,10
A	--- CA,A,2 056 859 (UNILEVER) 8 June 1992 cited in the application -----	2,7,11

☐ Further documents are listed in the continuation of box C.☒ Patent family members are listed in annex.

* Special categories of cited documents:

- *A* document defining the general state of the art which is not considered to be of particular relevance
- *E* earlier document but published on or after the international filing date
- *L* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- *O* document referring to an oral disclosure, use, exhibition or other means
- *P* document published prior to the international filing date but later than the priority date claimed

- *T* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- *X* document of particular relevance: the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- *Y* document of particular relevance: the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art
- *&* document member of the same patent family

Date of the actual completion of the international search

29 March 1995

Date of mailing of the international search report

04.04.95

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 cpo nl,
Fax (+31-70) 340-3016

Authorized officer

Rotsaert, L

INTERNATIONAL SEARCH REPORT

Intern: Application No.
PCT/US 94/13887

Patent document cited in search report	Publication date	Patent family member(s)	Publication date	
US-A-5188823	23-02-93	AU-A-	8289891	07-09-92
		CA-A-	2038789	08-08-92
		CN-A-	1063818	26-08-92
		EP-A-	0503180	16-09-92
		JP-A-	5112439	07-05-93
		WO-A-	9213516	20-08-92

US-A-5015415	14-05-91	AU-A-	6038290	11-03-91
		CA-A-	2019704	27-12-91
		WO-A-	9101970	21-02-91
		EP-A-	0486510	27-05-92
		EP-A-	0638072	15-02-95
		JP-T-	6501238	10-02-94
		JP-T-	4506538	12-11-92
		WO-A-	9200283	09-01-92

CA-A-2056859		NONE		
